

**Material Safety Data Sheet**

May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200. Standard must be consulted for specific requirements.

**US Department of Labor**

Occupational Safety and Health Administration  
Form Approved, OMB No. 1218-0072

Section I: Information**JET SET COMPLETE REPAIR**

Emergency Telephone Number, Jet Set Cement Corp. (510) 632-7800, (877) 239-7800

Date prepared: December, 2004

Section II: Hazardous Ingredients/Identity Information

Common Name(s)	CAS #	OSHA PEL	ACGIH TLV	Other	%
Calcium Salts - Cement	65997-15-1	10 mg/m3	10 mg/m3	None	N/A
Calcium Sulphate Hemihydrate	7778-18-9	5 mg/m3	10 mg/m3	None	N/A
Silica Sand	14808-60-7	0.1 mg/m3	0.1 mg/m3	None	N/A

15.0 mg/m3 TOTAL DUST

Section III - Physical/Chemical Characteristics

Boiling Point:	N/A	Specific Gravity (H2O = 1)	3.00
Vapor Pressure (mm Hg):	N/A	Melting Point:	N/A
Vapor Density (air = 1):	N/A	Evaporation Rate:	N/A
Solubility in Water:	Slight (0.1 - 1%)		
Appearance and Odor:	Grey (or white) powder, Odorless		

Section IV - Fire and Explosion Hazard

Flash Point (Method Used)	N/A		
Flammable Limits:	LEL	N/A	
	UEL	N/A	
Extinguishing Media:	None (Not Combustible)		
Special Fire Fighting Procedures:	None (Not Combustible)		
Unusual Fire and Explosion Hazards:	None (Not Combustible)		

Section V - Reactivity Data

Stability:	STABLE	Conditions to Avoid:	NONE
Hazardous Polymerization:	WILL NOT OCCUR	Conditions to Avoid:	NONE
Incompatibility (Materials to Avoid):			NONE

Section VI - Health Hazard Data

Route(s) of Entry: Inhalation? YES; Skin? YES; Ingestion? YES

Health Hazards (Acute and Chronic):

Extended respiration of crystalline silica may cause silicosis, a lung disorder which may be deadly. Wet Jet Set Complete Repair can cause dry skin and alkali burns. Cement dust can irritate the eyes and upper respiratory system.

Carcinogenicity:	NTP?	IARC Mamographs?	OSHA Regulated?
	YES	YES	NO

Respirable crystalline silica has been determined to be carcinogenic. Do not breathe dust.

Coughing, congestion, shortness of breath may be symptoms.

Signs and Symptoms of Exposure:

Dry skin, irritated nose or eyes, coughing, hard to breathe may be symptoms of cement dust exposure.

Medical Conditions Generally Aggravated by Exposure: NONE

Emergency and First Aid Procedures:

Irrigate eyes with water, wash affected areas of the body with soap and water, use hand-creams.

Section VII - Precautions for safe handling and use

Steps to be taken in Case Material is Released or Spilled: Use dry clean-up methods that avoid creating dust.

Waste Disposal Method: In accordance with local, state and federal regulations.

Precautions to be Taken in Handling and Storing: NONE

Other Precautions: NONE

